

INDUSTRIAL COMPONENT DATA

WML 7,5 (17X9)RL 1110065 PHOENIX CONTACT Cable marker label, Roll, white, unlabeled, can be labeled with: TH..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 7,5 (17X9)RL



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 7,5 (17X9)RL
Catalog number	1110065
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-6AA1B68E65
Generated	2026-08-04

Product Overview

Cable marker label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK S1.1, mounting type: adhesive, cable diameter: <= 7.5 mm, lettering field size: 17 x 9 mm, Number of individual labels: 5000

Cable wrapping label, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, cable diameter range: 2.9 ... 7.6 mm, cable diameter: <= 7.6 mm, usable area: 17x9mm, Number of individual indexes: 5000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1110065

Packing unit 1 pc

GTIN 4063151024437

Weight per Piece (excluding packing) 820.000 g

Custom tariff number 39199080

Country of origin DE (Germany)

Dimensions
General

Classifications

Ambient conditions

Standards and Regulations

Dimensions

Length (b) 35 mm

Width (a) 17 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -50 °C ... 110 °C

Recommended storage conditions 23 °C / 50% relative humidity. Storage in poly bags is recommended prior to processing.

[Back to top](#)General

Color white

Base element material Vinyl film

Type Label

Components Silicone-free

Material PVC

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 5000

Number of individual labels per row 4

Adhesive Acrylic

Printability Thermal transfer

Device 1085260 THERMOMARK ROLL 2.0

0804501 THERMOMARK ROLLMaster 300

0804663 THERMOMARK ROLLMaster 600

Ink ribbon 5145384 THERMOMARK-RIBBON 110

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Result of weather resistance test Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result of wipe resistance test Test passed

Foil strength 50 µm

Adhesive strength 25 µm

Marking mounting type adhesive

[Back to top](#)Sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 7,5 (17X9)RL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.