

INDUSTRIAL COMPONENT DATA

WMS 12,7 (30X20)R 0804266 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 12,7 (30X20)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 12,7 (30X20)R
Catalog number	0804266
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-0FCE912B6C
Generated	2026-08-05

Product Overview

Shrink sleeve

Heat-shrink tubing, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, Perforated, mounting class: slip, cable diameter range: 4.2 ... 12.7 mm, usable area: 30x20mm, Number of individual indexes: 500

Shrink sleeve, Roll, white, white, can be labelled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, perforated, mounting type: threaded, cable diameter: 4.2 ... 12.7 mm, Number of individual tags: 500, Height of the text field: 20 mm, Width of the text field: 30 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0804266

Packing unit 1 pc

Catalog page Page 232 (C-3-2017)

GTIN 4055626266817

Weight per Piece (excluding packing) 427.300 g

Custom tariff number 39173200

Country of origin US (United States)

Dimensions

Length (b) 30 mm

Width (a) 20 mm

Cable diameter 12.7 mm

General

Color white

Base element material polyolefine

Type Shrink sleeve

Components halogen-free

Material Polyolefine

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing without print

Number of individual labels 500

Number of individual labels per row 1

Marking mounting type slide on

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 4.1 24190219 eCl@ss 5.1 27400100 eCl@ss 6.0 27400100 eCl@ss 7.0 27400105 eCl@ss 8.0 27400105 eCl@ss 9.0 27400401

ETIM 4.0 EC000217 ETIM 5.0 EC000217 ETIM 6.0 EC001530

UNSPSC 13.2 39131504

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 12,7 (30X20)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.