

INDUSTRIAL COMPONENT DATA

WMS-2 HF 12,7 (EX20)R YE 0804521 PHOENIX CONTACT

Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 12,7 (EX20)R YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 12,7 (EX20)R YE
Catalog number	0804521
Category	Shrink tubing
Minimum order	1 Pcs
Document ID	EO-4ED79AAEDC
Generated	2026-08-04

Product Overview

Shrink sleeve

Heat shrink tubing, Roll, yellow, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, UNDRILLED, MOUNTING CLASS: SLIP, CABLE DIAMETER RANGE: 6.4 ... 12.7 mm, usable area: 20x20000mm, length. Roll: 20 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0804521

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 231 (C-3-2017)

GTIN 4055626399010

Weight per Piece (excluding packing) 555.000 g

Custom tariff number 39173200

Country of origin PL (Poland)

Dimensions

Length (b) 20 m

Width (a) 20 mm

Cable diameter 6.4 mm ... 12.7 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 105 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color yellow

Base element material polyolefine

Type Shrink sleeve

Components halogen-free

Material Polyolefine

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing without print

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146231 THERMOMARK X1.2

5146147 THERMOMARK W2

0804501 THERMOMARK ROLLMASTER 300

Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF

0801358 THERMOMARK-RIBBON 110-WMSU

0801360 THERMOMARK-RIBBON 64-WMSU

0803390 THERMOMARK-RIBBON 25-WMSU

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 12,7 (EX20)R YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.