

INDUSTRIAL COMPONENT DATA

WMS-2 HF 12,7 (EX20)RL BU CUS 8199181 PHOENIX CONTACT Cable marker, blue: user-defined, mounting type: slide..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 12,7 (EX20)RL BU CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 12,7 (EX20)RL BU CUS
Catalog number	8199181
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-7481A64A9F
Generated	2026-08-03

Product Overview

Cable marker, blue: user-defined, mounting type: slide on, lettering field size: max. 30 mm
Heat-shrink tubing, blue: customized, mounting class: sliding, usable surface: max. 30mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Cable marker, blue: user-defined, mounting type: slide on, lettering field size: max. 30 mm

Key Commercial Data

Orderkey 8199181

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626436753

Weight per Piece (excluding packing) 9.990 g

Custom tariff number 49119900

Country of origin PL (Poland)

Dimensions

Length (b) 80 mm

Width (a) 20 mm

General

Color blue

Type Shrink sleeve

Material Polyolefine

RoHS compliant Yes

Printing user-defined

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146231 THERMOMARK X1.2

5146147 THERMOMARK W2

0804501 THERMOMARK ROLLMASTER 300

0804663 THERMOMARK ROLLMASTER 600

Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF

0801358 THERMOMARK-RIBBON 110-WMSU

0801360 THERMOMARK-RIBBON 64-WMSU

0803390 THERMOMARK-RIBBON 25-WMSU

0804661 TM-RIBBON 110 WH 100

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Procedure

Test duration 96 h

Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Procedure A

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Test passed

Marking mounting type slide on

Oxygen index (DIN EN ISO 4589-2) 34.9 %

R22 HL 1 - HL 3

R23 HL 1 - HL 3

R24 HL 1 - HL 3

Standards and Regulations

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire prote...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 12,7 (EX20)RL BU CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.