

INDUSTRIAL COMPONENT DATA

WMS-2 HF 19,1 (30X30) RL YE 1086851 PHOENIX CONTACT

Shrink sleeve, roll, yellow, unmarked, 2:1 shrink ratio,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 19,1 (30X30) RL YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 19,1 (30X30) RL YE
Catalog number	1086851
Category	Cable coding system
Minimum order	5 Pcs
Document ID	EO-EF09E923F7
Generated	2026-08-05

Product Overview

Shrink sleeve, roll, yellow, unmarked, 2:1 shrink ratio, can be marked with: THERMOMARK ROLL, THERMOMARK X.1, perforated, mounting type: slid on

Heat shrink tubing, Roll, yellow, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2: without printing, Perforated, mounting class: slip, cable diameter range: 9.5 ... 19.1 mm, usable area: 30x30mm, number of individual indexes: 1000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1086851

Packing unit 1

GTIN 4055626881058

Custom tariff number 39173200

Dimensions

General

Classifications

Ambient conditions

Standards and Regulations

Dimensions

Length (b) 30 mm

Width (a) 30 mm

Cable diameter 19.1 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -30 °C ... 105 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

[Back to top](#)General

Color yellow

Base element material polyolefine

Type Shrink sleeve

Components halogen-free

Material Polyolefine

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing without print

Printability Thermal transfer

Device 1085260 THERMOMARK ROLL 2.0

5146147 THERMOMARK W2

0804501 THERMOMARK ROLLMaster 300

0804663 THERMOMARK ROLLMaster 600

Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF

0801358 THERMOMARK-RIBBON 110-WMSU

0801360 THERMOMARK-RIBBON 64-WMSU

0803390 THERMOMARK-RIBBON 25-WMSU

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Procedure

Test duration 96 h

Result of weather resistance test Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Procedure A

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result of wipe resistance test Test passed

Marki...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 19,1 (30X30) RL YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.