

INDUSTRIAL COMPONENT DATA

WMS-2 HF 4,8 (15X9)RL CUS 0833220 PHOENIX CONTACT

Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 4,8 (15X9)RL CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 4,8 (15X9)RL CUS
Catalog number	0833220
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-FC7F34C88E
Generated	2026-07-29

Product Overview

Shrink sleeve

Heat shrink tubing, Roll, white: custom, cut, mounting class: slip, cable diameter range: 2.4 ... 4.8 mm, usable surface: 15 x 9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > CABINET add-on**

Additional Product Information

Key Commercial Data

Orderkey 0833220

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626044873

Weight per Piece (excluding packing) 1.300 g

Custom tariff number 49119900

Country of origin DK (Denmark)

Dimensions

Length (b) 15 mm

Width (a) 9 mm

Cable diameter 2.4 mm ... 4.8 mm

Ambient conditions

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color white

Base element material polyolefine

Type Shrink sleeve

Components halogen-free

Material Polyolefine

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing user-defined

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146231 THERMOMARK X1.2

5146147 THERMOMARK W2

0804501 THERMOMARK ROLLMaster 300

Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF

0801358 THERMOMARK-RIBBON 110-WMSU

0801360 THERMOMARK-RIBBON 64-WMSU

0803390 THERMOMARK-RIBBON 25-WMSU

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type slide on

Oxygen index (DIN EN ISO 4589-2) 34.9 %

R22...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 4,8 (15X9)RL CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.