

INDUSTRIAL COMPONENT DATA

WMTB HF (40X12)R OG 1097009 PHOENIX CONTACT Cable marker, Roll, orange, unlabeled, can be labeled with: THER..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB HF (40X12)R OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB HF (40X12)R OG
Catalog number	1097009
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-D185E8C6D5
Generated	2026-08-04

Product Overview

Cable marker, Roll, orange, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: Assembly with cable binders, cable diameter: ≥ 6 mm, lettering field size: 40 x 12 mm, Number of individual labels: 1000

Cable marker, Roll, orange, unlabeled, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: Mounting with cable tie, cable diameter: ≥ 6 mm, useful surface: 40 x 12 mm, Number of individual indexes: 1000

Cable marker, Roll, orange, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: Assembly with cable ties, cable diameter: ≥ 6 mm, Number of individual labels: 1000, text field height: 12 mm, text field width: 40 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking

Type Roll

Data management status

Article revision 00

Marking

Number of individual labels 1000

Number of individual labels per row 1
Identification technology Thermal transfer for rolls
Dimensions Width 12 mm
Text field width 40.00 mm
Text field height 12.00 mm
Length 40 mm
External dimensions
Outside diameter 6 mm ... 136 mm
Material specifications RoHS compliant yes
Color orange (RAL 2003)
Material PUR
Flammability rating according to UL 94 V2 (0,75 mm Wandstärke)
Components halogen-free
Cable/line External cable diameter ≥ 6.00 mm
Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements ≥ 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 125 °C (150 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-03
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Test passed
Ethano...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB HF (40X12)R OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.