

INDUSTRIAL COMPONENT DATA

WMTB HF (40X18)R BK 1369835 PHOENIX CONTACT Cable marker, Roll, black, unlabelled, labelable with: THERMOMAR..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB HF (40X18)R BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB HF (40X18)R BK
Catalog number	1369835
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-467A99F64A
Generated	2026-08-06

Product Overview

Cable marker, Roll, black, unlabelled, labelable with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: Mounting with cable tie, cable diameter: ≥ 6 mm, Number of individual indexes: 1000, text field height: 18 mm, text field width: 40 mm

Cable marker, Roll, black, unlabeled, labelable with: THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: Mounting with cable ties, cable diameter: ≥ 6 mm, usable area: 40x18mm, Number of individual indexes: 1000

Cable marker, Roll, black, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: Assembly with cable ties, cable diameter: ≥ 6 mm, lettering field size: 40 x 18 mm, Number of individual labels: 1000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking

Type Roll

Marking

Number of individual labels 1000

Number of individual labels per row 3

Identification technology Thermal transfer for rolls

DimensionsWidth 18 mm

Length 40 mm

Material specificationsColor black

Flammability rating according to UL 94 V2 (0,75 mm Wandstärke)

Components halogen-free

Cable/lineExternal cable diameter ≥ 6 mm

Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 125 °C (150 °C) Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Diesel

[CAS No. 68476-34-6] Test passed

IRM 901 Test passed

IRM 902 Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification DIN 50018:2013-05

Result Test passed

Climate level AHT 1.0 S

Cycles 2

Salt spray test

Specification DIN EN 60068-2-11:2000-02

Result Test passed

Test duration 96 h

Ambient conditions

Ambient temperature (operation) -25 °C ... 100 °C

Recommended ambient temperature (storage/transport) 10 °C ... 25....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB HF (40X18)R BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.