

## INDUSTRIAL COMPONENT DATA

# TOOL-WRAP-2 1200100 PHOENIX CONTACT Tool bag, equipped

Brand: PHOENIX CONTACT | Manufacturer Part Number: TOOL-WRAP-2



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | PHOENIX CONTACT |
| MPN / Reference | TOOL-WRAP-2     |
| Catalog number  | 1200100         |
| Category        | Tool set        |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-6AC36E07BB   |
| Generated       | 2026-08-02      |

## Product Overview

Tool bag, equipped

Tool bag, equipped with: cable cutter, wire stripper tool for standard conductors 0.08 mm<sup>2</sup> ... 16 mm<sup>2</sup>, tool for de-insulating up to Ø 40 mm, CRIMPFOX CENTRUS 6H dropout pliers for conductors 0.14 mm<sup>2</sup> ... 6 mm<sup>2</sup>, VDE screwdriver, narrow version, slot: 0.6x3.5/0.8x4.0/1.0x5.5, cross: PH1/PH2/PZ1/PZ2

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                            |
|--------------|----------------------------|
| Catalog path | PHOENIX CONTACT > TOOL fox |
|--------------|----------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1200100

Packing unit 1 pc

Catalog page Page 465 (C-3-2017)

GTIN 4055626030715

Weight per Piece (excluding packing) 2,764.000 g

Custom tariff number 82060000

Country of origin DE (Germany)

Environmental Product Compliance

California Proposition 65 Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

Articles in set

Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm<sup>2</sup> ... 6 mm<sup>2</sup>, also for TWIN ferrules up to 2 x 4 mm<sup>2</sup>, automatic cross section adjustment, lateral insertion, equipped with fall protection

Cable cutter, angled, for copper and aluminum up to 18 mm diameter (up to 50 mm<sup>2</sup>)

Stripping tool, for cables and conductors from 0.02 - 10 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

Stripping pliers, for cables and conductors with a cross section of 6 - 16 mm<sup>2</sup>, self-adjusting, any stripping length, also suitable for sensor/actuator cables

Stripping tool, for stripping cables of 4.5 mm - 40 mm-Ø, insulation thickness of up to 4.5 mm, pivoting blade for round, lengthwise, and spiral cuts

Screwdriver set, protective insulation integrated in the shaft, bladed/crosshead Phillips/combined profile, Pozidriv®+ bladed (plus/minus), VDE-insulated, 7-part, incl. rack, set contains the following items: 0.6 x 3.5 x 100, 0.8 x 4.0 x 100, 1.0 x 5.5 x 125, PH1 x 80, PH2 x 100,....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TOOL-WRAP-2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.