

**INDUSTRIAL COMPONENT DATA**

# XT 2,5 OG 1741334 PHOENIX CONTACT Feed-through terminal, nominal voltage: 800 V, nominal current: 24 A, numb..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: XT 2,5 OG**

|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | XT 2,5 OG                   |
| Catalog number  | 1741334                     |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-3D7E4764BB               |
| Generated       | 2026-08-02                  |

## Product Overview

Feed-through terminal, nominal voltage: 800 V, nominal current: 24 A, number of connections: 2, number of poles: 1, connection type: Push-X connection, Dimensioning cross-section: 2.5 mm<sup>2</sup>, cross-section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, colour: orange

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / XT 2,5 OG with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.