

INDUSTRIAL COMPONENT DATA

XT 2,5-QUATTRO BU 1343130 PHOENIX CONTACT

Feed-through terminal, nominal voltage: 800 V, nominal current: 24..

Brand: PHOENIX CONTACT | Manufacturer Part Number: XT 2,5-QUATTRO BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	XT 2,5-QUATTRO BU
Catalog number	1343130
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-CFABADE613
Generated	2026-08-04

Product Overview

Feed-through terminal, nominal voltage: 800 V, nominal current: 24 A, number of connections: 4, number of poles: 1, connection type: Push-X connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.5 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral

Observation The maximum load current must not be exceeded by the total current of all connected conductors.

Item PropertiesProduct Type Multi-conductor terminal block

Number of poles 1

Field of Employment Railway industry

Machine building

Plant construction

Process Industry

Number of connections 4

Number of rows 1

Potential 1

Insulation Properties

Surge Category Iii

Degree of pollution 3

Electrical Properties Dimensioning Transient Voltage 8 kV

Maximum Dissipated Power with Nominal Condition 0.77 W

Connection data Number of connections per floor 4

Nominal Section 2.5 mm²

AWG Conductor Section (Converted according to IEC)

Peel Length 10 mm ... 12 mm

Standard-compliant connection IEC 60947-7-1

Rigid conductor section 0.5 mm² ... 4 mm²

AWG Conductor Section 20 ... 12 (Converted according to IEC)

Flexible conductor section 0.75 mm² ... 4 mm²

Flexible Wire Section [AWG] 18 ... 12 (Converted according to IEC)

Flexible cable section (toe cap without plastic sleeve) 0.5 mm² ... 2.5 mm²

Flexible cable section (toe cap with plastic sleeve) 0.5 mm² ... 2.5 mm²

Nominal current 24 A

Maximum Charging Current 28 A (with rigid 4 mm² cable cross-section)

Nominal voltage 800 V

Nominal Section 2.5 mm²

Dimensions Width 5.2 mm

Height 72.2 mm

Depth 35.3 mm

Depth at NS 35/7.5 36.8 mm

Depth at NS 35/15 44.3 mm

Material Data Colour blue

Flammability class according to UL 94 V0

Insulating material group I

Insulating material PA

Static use of cold insulating material -60 °C

Rela...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / XT 2,5-QUATTRO BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.