

**INDUSTRIAL COMPONENT DATA**

# XTV 16 1329672 PHOENIX CONTACT Feed-through terminal, nominal voltage: 1000 V, nominal current: 76 A, number..

Brand: PHOENIX CONTACT | Manufacturer Part Number: XTV 16



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | XTV 16                      |
| Catalog number  | 1329672                     |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-28DFF2ADAC               |
| Generated       | 2026-08-02                  |

## Product Overview

Feed-through terminal, nominal voltage: 1000 V, nominal current: 76 A, number of connections: 2, number of poles: 1, connection type: Push-X connection, Dimensioning cross-section: 16 mm<sup>2</sup>, cross-section: 2.5 mm<sup>2</sup> - 25 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, colour: grey

Pass-through terminal

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

ETIM for 1329672 Terminal blocks (EC000897)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

4 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

2.5 mm<sup>2</sup>

Connectable conductor cross section solid-core (EF007337)

2.5 mm<sup>2</sup>

Rated current I<sub>n</sub> (EF008250)

76 A

Rated voltage (EF000228)

1000 V  
Type of electrical connection 1 (EF002526)  
Other  
Type of electrical connection 2 (EF002527)  
Other  
Number of clamp positions per level (EF002660)  
2  
Suitable for conductor material (EF012572)  
Aluminium/copper  
Mounting method (EF000003)  
DIN rail (top hat rail) 35 mm  
Material insulation body (EF007543)  
Other  
Operating temperature (EF002393)  
-60 °C  
Inflammability class of insulation material according to UL94 (EF002521)  
V0  
Width (EF000008)  
12.2 mm  
Height (EF000040)  
77.2 mm  
Depth (EF000049)  
49.8 mm  
Closing plate required (EF002525)  
Yes  
Colour (EF000007)  
Grey  
Internally connected stages (EF002661)  
Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / XTV 16 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.