

INDUSTRIAL COMPONENT DATA

SAC-4PY-MT/2XFT VP 1410632 PHOENIX CONTACT Y distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4PY-MT/2XFT VP



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4PY-MT/2XFT VP
Catalog number	1410632
Category	Sensor actuator adapter
Minimum order	5 Pcs
Document ID	EO-1C4DC5ED4F
Generated	2026-08-04

Product Overview

Y distributor

Y-splitter, 4-pole, M12 straight connector, encoding: T, to M12 straight female, encoding: T and M12 straight female, coding: T, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1410632

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 302 (C-2-2017)

GTIN 4046356924726

Weight per Piece (excluding packing) 38.360 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Center distance 21 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 80 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 2x 12 A (at 40 °C)

Rated voltage 63 V DC

Number of positions 4

Color handle area black

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding T power

Standards/regulations M12 connector IEC 61076-2-111

Status display No

Overvoltage category III

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-111

Flammability rating according to UL 94 HB

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Classifications

eCl@ss 5.127061800eCl@ss 6.027279200eCl@ss 7.027440104eCl@ss 8.027440104eCl@ss 9.027440106

ETIM 4.0EC001855ETIM 5.0EC002062ETIM 6.0EC002925

UNSPSC 13.231251501

ETIM for 1410632 Sensors (EC002925)

Feature Name

Feature Value

Model (EF000010)

Y-adapter

Screened (EF000881)

No

Housing mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4PY-MT/2XFT VP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.