

INDUSTRIAL COMPONENT DATA

SAC-3P-M 8Y/2XM 8FS VP 1696222 PHOENIX CONTACT Y distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M 8Y/2XM 8FS VP



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M 8Y/2XM 8FS VP
Catalog number	1696222
Category	Sensor actuator adapter
Minimum order	5 Pcs
Document ID	EO-182A783BBC
Generated	2026-08-05

Product Overview

Y distributor

Y-splitter, 3-pole, unshielded, M8 straight connector, encoding: A, a M8 straight female, coding: A and M8 straight female, coding: A, parallel purge nozzle

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1696222

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 259 (C-2-2017)

GTIN 4017918182403

Weight per Piece (excluding packing) 6.810 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Center distance 12 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 3

Insulation resistance ≥ 10 G?

Coding A - standard

Standards/regulations M8 connector IEC 61076-2-104

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.2 Nm (M8 connectors)

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 HB

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127061800eCl@ss 6.027279200eCl@ss

7.027440104eCl@ss 8.027440104eCl@ss 9.027440106

ETIM 2.0EC000830ETIM 3.0EC001856ETIM 4.0E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M 8Y/2XM 8FS VP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.