


INDUSTRIAL COMPONENT DATA

ZB 5,LGS:L1-N,PE 1050415 PHOENIX CONTACT Zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZB 5,LGS:L1-N,PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZB 5,LGS:L1-N,PE
Catalog number	1050415
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-3694077597
Generated	2026-08-06

Product Overview

Zack marker strip

Zack tape strip, Strips, white, labeled, longitudinal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting class: interlock, for terminal width: 5.2 mm, usable surface: 5.15x10.5mm, Number of individual indexes: 10

Zack Tape Strip, Strips, white, labeled, longitudinal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting class: interlock, for terminal width: 5.2 mm, Number of individual indexes: 10, text field height: 10.5 mm, text field width: 5.15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data

Orderkey 1050415

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 125 (C-3-2017)

GTIN 4017918015701

Weight per Piece (excluding packing) 1.070 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Width (a) 5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

General

Note 10 identically marked strips make up one packing unit (PU).

Color white

Type high

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing direction Horizontal

Printing L1, L2, L3, N, PE, L1, L2, L3, N, PE

Number of individual labels 10

Number of individual labels per row 10

Number of marker strips 10

Marking mounting type snap into tall marker groove

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Flammability rating according to UL 94 V2

Classifications

eCl@ss 4.024190208eCl@ss 4.124190208eCl@ss 5.027149103eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss
7.027141137eCl@ss 8.027141137eCl@ss 9.027141137

ETIM 2.0EC000761ETIM 3.0EC000761ETIM 4.0EC000761ETIM 5.0EC000761ETIM 6.0EC000761

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC 12.0139121410UNSPSC
13.239131505

ETIM for 1050415 Terminal blocks (EC000761)

Feature Name**Feature Value**

Imprint (EF000131)

Other

Modular spacing (EF000394)

5.2 mm

Colour (EF000007)

White

Halogen free (EF000025)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZB 5,LGS:L1-N,PE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.