

INDUSTRIAL COMPONENT DATA

ZBF 15:UNBEDRUCKT 0811202 PHOENIX CONTACT Zack Marker strip, flat

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZBF 15:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZBF 15:UNBEDRUCKT
Catalog number	0811202
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-05A32C742B
Generated	2026-08-05

Product Overview

Zack Marker strip, flat

Zack flat tape strip, Strips, white, unlabeled, labelable with: PLOTMARK, CMS-P1-PLOTTER, mounting class: interlock, for terminal width: 15 mm, useful surface: 15x5.2mm, Number of individual indexes: 5

Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 15 mm, Number of individual labels: 5, text field height: 5.2 mm, text field width: 15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Terminal marking

Pitch 15 mm

Type flat

Data management status

Article revision 00

Marking

Number of individual labels 5

Number of individual labels per row 5

Number of marker strips 10

DimensionsWidth 15 mm

Text field width 15.00 mm

Text field height 5.20 mm
Pitch 15 mm
Material specificationsColor white (RAL 9010)
Material PA
Flammability rating according to UL 94 V2
Components free from silicone and halogen
Environmental and real-life conditionsUV resistance
Specification ISO 4892-2:2013-03 (following)
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Ambient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Recommended ambient temperature (storage/transport) 23 °C
Recommended humidity (storage/transport) 50 %
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
MountingMounting type latching

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZBF 15:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.