

INDUSTRIAL COMPONENT DATA

ZBF 8:UNBEDRUCKT 0808781 PHOENIX CONTACT Zack Marker strip, flat

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZBF 8:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZBF 8:UNBEDRUCKT
Catalog number	0808781
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-F4191C8C95
Generated	2026-08-03

Product Overview

Zack Marker strip, flat

Flat Zack tape strip, Strips, white, unlabeled, labelable with: PLOTMARK, CMS-P1-PLOTTER, mounting class: interlock, for terminal width: 8 mm, useful surface: 5.15x8.15mm, Number of individual indexes: 10

Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 8 mm, Number of individual labels: 10, text field height: 8.15 mm, text field width: 5.15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Terminal marking

Pitch 8 mm

Type flat

Data management status

Article revision 01

Marking

Number of individual labels 10

Number of individual labels per row 10

Number of marker strips 10

DimensionsWidth 8 mm

Text field width 5.15 mm

Text field height 8.15 mm
Pitch 8 mm
Material specificationsColor white (RAL 9010)
Material PA
Flammability rating according to UL 94 V2
Components free from silicone and halogen
Environmental and real-life conditionsUV resistance
Specification ISO 4892-2:2013-03 (following)
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Ambient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Recommended ambient temperature (storage/transport) 23 °C
Recommended humidity (storage/transport) 50 %
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
MountingMounting type latching

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZBF 8:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.