

**INDUSTRIAL COMPONENT DATA**

# ZB 15/RD-100:UNPRINTED 0815237 PHOENIX CONTACT Zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZB 15/RD-100:UNPRINTED



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | PHOENIX CONTACT              |
| MPN / Reference | ZB 15/RD-100:UNPRINTED       |
| Catalog number  | 0815237                      |
| Category        | Labelling for terminal block |
| Minimum order   | 100 Pcs                      |
| Document ID     | EO-11FF5BF243                |
| Generated       | 2026-08-04                   |

## Product Overview

Zack marker strip

Zack Strip, Strips, red, unlabeled, labelable with: PLOTMARK, CMS-P1-PLOTTER, mounting class: fit, for terminal width: 15.2 mm, useful surface: 10.5 x 15.1 mm, Number of individual indexes: 500

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0815237

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356073561

Weight per Piece (excluding packing) 3.130 g

Custom tariff number 39269097

Country of origin DE (Germany)

Dimensions

Width (a) 15 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

**General**

Color red

Type high

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 5

Number of individual labels per row 5

Number of marker strips 5

Marking mounting type snap into tall marker groove

**Standards and Regulations**

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Flammability rating according to UL 94 V2

**Classifications**eCl@ss 4.024190208eCl@ss 4.124190208eCl@ss 5.027149103eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss  
7.027141137eCl@ss 8.027141137eCl@ss 9.027141137

ETIM 2.0EC000761ETIM 3.0EC000761ETIM 4.0EC000761ETIM 5.0EC000761ETIM 6.0EC000761

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC 12.0139121410UNSPSC  
13.239131505**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / ZB 15/RD-100:UNPRINTED with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.