

INDUSTRIAL COMPONENT DATA

ZB 5,LGS:1-9 1050127 PHOENIX CONTACT Zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZB 5,LGS:1-9



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZB 5,LGS:1-9
Catalog number	1050127
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-768D1A6CDF
Generated	2026-08-03

Product Overview

Zack marker strip

Zack Tape Strip, Strips, White, Lettering, Longitudinal Lettering: Correlative Numbers 1 ... 9, Mounting class: locking, for terminal width: 5.2 mm, usable area: 5.15x10.5mm, Number of individual indexes: 10

Zack Tape, Stripe, White, Initialled, Longitudinal Marking: Progressive Numbers 1 ... 9, Mounting type: locking, for terminal blocks with thickness: 5.2 mm, Number of individual tags: 10, Height of the text field: 10.5 mm, Width of the text field: 5.15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1050127

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4017918015565

Weight per Piece (excluding packing) 1.000 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Width (a) 5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

General

Note 10 identically marked strips make up one packing unit (PU).

Color white

Type high

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

DIN VDE 0611

Printing direction printed horizontally

Printing consecutive numbers 1 ... 9

Number of individual labels 10

Number of individual labels per row 10

Number of marker strips 10

Marking mounting type snap into tall marker groove

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

DIN VDE 0611

Flammability rating according to UL 94 V2

Classifications

eCl@ss 4.024190208eCl@ss 4.124190208eCl@ss 5.027149103eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss
7.027141137eCl@ss 8.027141137eCl@ss 9.027141137

ETIM 2.0EC000761ETIM 3.0EC000761ETIM 4.0EC000761ETIM 5.0EC000761ETIM 6.0EC000761

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC 12.0139121410UNSPSC
13.239131505

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZB 5,LGS:1-9 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.