

INDUSTRIAL COMPONENT DATA

ZBFM 8/WH:UNBEDRUCKT 0800734 PHOENIX CONTACT Flat zack marker sheet

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZBFM 8/WH:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZBFM 8/WH:UNBEDRUCKT
Catalog number	0800734
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-A2E4D7DB72
Generated	2026-08-05

Product Overview

Flat zack marker sheet

Zack flat strip sheet, Mat, white, unlabeled, labelable with: CMS-P1-PLOTTER, PLOTMARK, mounting class: interlock, for terminal width: 8.2 mm, useful surface: 5x8mm, Number of individual indexes: 50

Flat zack marker sheet, Sheet, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: latching, for terminal block width: 8.2 mm, Number of individual labels: 50, text field height: 5 mm, text field width: 8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral Can be labeled with CMS

Product propertiesProduct type Terminal marking

Pitch 8.2 mm

Type flat

Data management status

Article revision 00

Marking

Number of individual labels 50

Number of individual labels per row 5

Number of marker strips 10

DimensionsWidth 8 mm

Text field width 8.00 mm
Text field height 5.00 mm
Pitch 8.2 mm
Material specificationsColor white (RAL 9010)
Material PA
Flammability rating according to UL 94 V2
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 100 °C
Relative insulation material temperature index (Elec., UL 746 B) 125 °C
Components free from silicone and halogen
Environmental and real-life conditionsUV resistance
Specification ISO 4892-2:2013-03 (following)
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Ambient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Recommended ambient temperature (storage/transport) 23 °C
Recommended humidity (storage/transport) 50 %
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
MountingMounting type latching

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZBFM 8/WH:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.