


INDUSTRIAL COMPONENT DATA

ZEC 1,5/ 2-ST-5,0 C1,2 R1,2 1756605 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZEC 1,5/ 2-ST-5,0 C1,2 R1,2



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZEC 1,5/ 2-ST-5,0 C1,2 R1,2
Catalog number	1756605
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-C9DB8190D6
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Direct connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 10 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Female connection, Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, number of connections: 2, family of articles: ZEC 1.5/..-ST, pitch: 5 mm, connection type: Spring connection, mounting: Direct plug-in connection technique, conductor connection direction/printed circuit board: 0 °, Stecksystem: ZEC, Locking: Snap lock, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1756605

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356337434

Weight per Piece (excluding packing) 3.390 g

Custom tariff number 85366930

Country of origin GR (Greece)

Dimensions

Pitch 5 mm

Dimension a 5 mm

General

Range of articles ZEC 1,5/...-ST

Number of positions 2

Connection method Spring-cage connection

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 10 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 0.5 mm²

Minimum AWG according to UL/CUL 26

Maximum AWG according to UL/CUL 14

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally frie...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZEC 1,5/ 2-ST-5,0 C1,2 R1,2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.