

INDUSTRIAL COMPONENT DATA

ZEC 1,5/ 5-LPV-7,5 OHNE CODIER 1972360 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZEC 1,5/ 5-LPV-7,5 OHNE CODIER



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZEC 1,5/ 5-LPV-7,5 OHNE CODIER
Catalog number	1972360
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-B12C0DAC2F
Generated	2026-08-03

Product Overview

PCB connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 10 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: ZEC 1.5/.. -LPV, pitch: 7.5 mm, mounting: Direct plug-in connection technology, driver/printed circuit board connection direction: 0 °, number of solder pins per potential: 2, plug-in system: ZEC, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross-section: 1.5 mm², colour: green, rated current: 10 A, dimensioning voltage (III/2): 630 V, contact surface: Sn, contact connection type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, product series: ZEC 1.5/.. -LPV, pitch: 7.5 mm, mounting: Direct connection, conductor/board connection direction: 0°, number of solder pins per potential: 2, plug system: ZEC, locking: none, fastening type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1972360

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918937744

Weight per Piece (excluding packing) 5.100 g

Custom tariff number 85366990

Country of origin BG (Bulgaria)

Dimensions

Pitch 7.5 mm

Dimension a 30 mm

General

Range of articles ZEC 1,5/..-LPV

Connection in acc. with standard EN-VDE

Nominal current IN 10 A

Nominal voltage UN 400 V

Nominal cross section 1.5 mm²

Number of positions 5

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

ETIM for 1972360 Connectors (EC002637)

Feature Name

Feature Value

Contact type (EF001587)

Bus

Number of poles (EF001391)

5

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

7.5 mm

Modular spacing connections (EF006827)

7.5 mm

Rated current In (EF008250)

10 A

Rated voltage (EF000228)

630 V

Rated surge voltage (EF002993)

6 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Material insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZEC 1,5/ 5-LPV-7,5 OHNE CODIER with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.