


INDUSTRIAL COMPONENT DATA

ZEC 1,5/6-ST-5,0BKC2R1,6PW:1-6 1707330 PHOENIX CONTACT PCB connector, nominal current: 10 A, rated voltage (..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZEC 1,5/6-ST-5,0BKC2R1,6PW:1-6



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZEC 1,5/6-ST-5,0BKC2R1,6PW:1-6
Catalog number	1707330
Category	Cable connector
Minimum order	2000 Pcs
Document ID	EO-CE4B9B3BA7
Generated	2026-08-04

Product Overview

PCB connector, nominal current: 10 A, rated voltage (III/2): 320 V, nominal cross section: 1.5 mm², number of positions: 6, pitch: 5 mm, connection method: Spring-cage connection, color: signal violet, contact surface: Tin, mounting: Direct plug-in method

Direct connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 10 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact connection type: Female, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: ZEC 1.5/.. -ST, pitch: 5 mm, connection type: Spring connection, mounting: Direct plug-in connection technology, driver/printed circuit board connection direction: 0 °, plug-in system: ZEC, locking: Snap-in lock, fixing type: Snap-in flange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1707330

Packing unit 1 pc

GTIN 4046356919296

Weight per Piece (excluding packing) 200.000 g

Custom tariff number 85366930

Country of origin GR (Greece)

Drawings

General

Classifications

Dimensions

Environmental Product Compliance

Drawings

Diagram

Type: ZEC 1,5/...-ST-5,0

[Back to top](#)Dimensions

Pitch 5 mm

[Back to top](#)General

Range of articles ZEC 1,5/...-ST

Number of positions 6

Nominal cross section 1.5 mm²

[Back to top](#)Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)Classifications

eCl@ss

eCl@ss 4.0 27260700

eCl@ss 4.1 27260700

eCl@ss 5.0 27260700

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440309

eCl@ss 8.0 27440309

eCl@ss 9.0 27440309

[Back to top](#)ETIM

ETIM 4.0 EC002638

ETIM 5.0 EC002638

ETIM 6.0 EC002638

ETIM 7.0 EC002638

[Back to top](#)UNSPSC

UNSPSC 13.2 39121409

UNSPSC 18.0 39121409

UNSPSC 19.0 39121409

UNSPSC 20.0 39121409

UNSPSC 21.0 39121409

[Back to top](#)

ETIM for 1707330 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of poles (EF001391)

6

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5 mm

Modular spacing connections (EF006827)

5 mm

Angle contact/conductor connection (EF007546)

Other

Rated current I_n (EF008250)

10 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution d...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZEC 1,5/6-ST-5,0BKC2R1,6PW:1-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.