

## INDUSTRIAL COMPONENT DATA

# ZFK3DSA 1,5-5,08-24 BU BDWH M8 1807188 PHOENIX

## CONTACT PCB terminal block, nominal current: 12 A, nom. volta..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFK3DSA 1,5-5,08-24 BU BDWH M8



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | ZFK3DSA 1,5-5,08-24 BU BDWH M8 |
| Catalog number  | 1807188                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 10 Pcs                         |
| Document ID     | EO-D41EBD95B0                  |
| Generated       | 2026-08-03                     |

### Product Overview

PCB terminal block, nominal current: 12 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 24, connection method: Spring-cage connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: blue

Terminal block for printed circuit board, nominal current: 12 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm<sup>2</sup>, number of potentials: 72, number of rows: 3, number of poles per row: 24, article family: ZFK3DS(A) 1.5, pitch: 5.08 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: blue, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, number of welding pins per potential: 1, packaging type: boxed

PCB terminal block, nominal current: 12 A, rated voltage (III/2): 400 V, nominal cross section: 1.5 mm<sup>2</sup>, pitch: 5.08 mm, number of positions: 24, connection method: Spring-cage connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: blue, Pin layout: Linear pinning, Solder pin [P]: 3.4 mm

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Key Commercial Data  
Orderkey 1807188  
Packing unit 1  
GTIN 4046356701112

Custom tariff number 85369010

Item properties

Connection capacity

Material data - housing

Dimensions for PCB design

Ambient conditions

Air clearances and creepage distances

Environmental Product Compliance

Electrical parameters

Material data - contact

Dimensions for the product

Packaging information

Electrical tests

Standards and Regulations

Classifications

Item properties

Brief article description PCB terminal block

Range of articles ZFK3DS(A) 1,5

Pitch 5.08 mm

Number of positions 24

Connection method Spring-cage connection

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 3

Number of connections 72

Number of potentials 72

[Back to top](#)Electrical parameters

Nominal current 12 A

Nom. voltage 400 V

Rated voltage 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

[Back to top](#)Connection capacity

Connection method Spring-cage connection

pluggable Yes

Conductor cross section solid 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section flexible 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

Conductor cross section AWG / kcmil 24 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

Stripping length 7.5 mm

[Back to top](#)Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFK3DSA 1,5-5,08-24 BU BDWH M8 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.