


INDUSTRIAL COMPONENT DATA

ZFKDSA 1-3,81-21 1932892 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKDSA 1-3,81-21



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKDSA 1-3,81-21
Catalog number	1932892
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-56CF6A0CF9
Generated	2026-08-03

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 12 A, rated voltage (III/2): 200 V, nominal cross-section: 1 mm², number of potentials: 21, number of rows: 1, number of poles per row: 21, article family: ZFKDS(A) 1, pitch: 3.81 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed

Printed circuit board terminal, nominal current: 12 A, rated voltage (III/2): 200 V, nominal cross section: 1 mm², number of potentials: 21, number of rows: 1, number of positions per row: 21, product range: ZFKDS(A) 1, pitch: 3.81 mm, connection method: Spring-cage connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 2, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family ZFKDS(A) 1

Product line COMBICON Terminals S

Type PC terminal block can be aligned

Number of positions 21

Pitch 3.81 mm
Number of connections 21
Number of rows 1
Number of potentials 21
Pin layout Linear pinning
Solder pins per potential 2
Data management status
Article revision 00
Electrical propertiesNominal current I_N 12 A
Nominal voltage U_N 200 V
Rated voltage (III/3) 200 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 200 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 400 V
Rated surge voltage (II/2) 2.5 kV
Connection dataConnection technology
Type PC terminal block can be aligned
Nominal cross section 1 mm²
Conductor connection
Connection method Spring-cage connection
Conductor cross section rigid 0.14 mm² ... 1.5 mm²
Conductor cross section flexible 0.14 mm² ... 1 mm²
Conductor cross section AWG 26 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.5 mm²
Stripping length 7.5 mm
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics hot-dip tin-plated
Metal surface terminal point (top layer) Tin (10 - 16 µm Sn)
Metal surface soldering area (t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKDSA 1-3,81-21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.