

INDUSTRIAL COMPONENT DATA

ZFKDSA 1-V-6,35 1707357 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKDSA 1-V-6,35



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKDSA 1-V-6,35
Catalog number	1707357
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-69F41B9C20
Generated	2026-08-02

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 12 A, nominal voltage (III/2): 200 V, nominal cross-section: 1 mm², number of potentials: 1, number of rows: 1, number of poles per row: 1, article family: ZFKDS(A) 1-V, pitch: 3.81 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of welding pins per potential: 2, packaging type: boxed packaging. Terminal terminal for the termination of individually compound blocks.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1707357

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 41 (CC-2005)

GTIN 4017918144791

Weight per Piece (excluding packing) 1.660 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [L] 15.9 mm

Pitch 3.81 mm

Height 16 mm

Solder pin [P] 3.5 mm

Hole diameter 1.2 mm

General

Range of articles ZFKDS(A) 1-V

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 200 V

Rated voltage (III/2) 200 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 1 mm²

Solder pin surface

Stripping length 7.5 mm

Number of positions 1

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

2 conductors with same cross section, stranded min. 0.14 mm²

2 conductors with same cross section, stranded max. 0.2 mm²

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0271411109eCl@ss 4.1271411109eCl@ss 5.0271411190eCl@ss 5.1272611100eCl@ss 6.0272611100eCl@ss

7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC

13.239121432

ETIM for 1707357 Connecto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKDSA 1-V-6,35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.