

**INDUSTRIAL COMPONENT DATA**

# ZFKDSA 4-7,5- 3 GNYE BDNZ3104 1932481 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKDSA 4-7,5-3 GNYE BDNZ3104



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | ZFKDSA 4-7,5-3 GNYE BDNZ3104   |
| Catalog number  | 1932481                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-A87C3485DD                  |
| Generated       | 2026-08-06                     |

## Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 32 A, rated voltage (III/2): 630 V, rated cross-section: 4 mm<sup>2</sup>, number of potentials: 3, number of rows: 1, number of poles per row: 3, article family: ZFKDS(A) 4, pitch: 7.5 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: multicolor, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.6 mm, number of solder pins per potential: 2, packaging type: boxed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

## Additional Product Information

Key Commercial Data

Orderkey 1932481

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918858223

Weight per Piece (excluding packing) 14.020 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [ L ] 29 mm

Pitch 7.5 mm

Dimension a 15 mm

Height 23 mm

Solder pin [P] 4.6 mm

Hole diameter 1.8 mm

General

Range of articles ZFKDS(A) 4

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 32 A

Nominal cross section 4 mm<sup>2</sup>

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A4

Stripping length 10 mm

Number of positions 3

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141109eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss

7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKDSA 4-7,5-3 GNYE BDNZ3104 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.