

INDUSTRIAL COMPONENT DATA

ZFKKDSA 2,5-5,08- 8 BKBDWH18-31 1702873 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKKDSA 2,5-5,08- 8 BKBDWH18-31



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKKDSA 2,5-5,08- 8 BKBDWH18-31
Catalog number	1702873
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-5E07B2472B
Generated	2026-08-06

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 2.5 mm², Number of potentials: 16, Number of rows: 2, Number of poles per row: 8, article family: ZFKKDS(A) 2,5, pitch: 5.08 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed

Printed circuit board terminal, nominal current: 17.5 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², number of potentials: 16, number of rows: 2, number of positions per row: 8, product range: ZFKKDS(A) 2,5, pitch: 5.08 mm, connection method: Spring-cage connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family ZFKKDS(A) 2,5

Product line COMBICON Terminals M

Type PC terminal block can be aligned

Number of positions 8

Pitch 5.08 mm

Number of connections 16
Number of rows 2
Number of potentials 16
Pin layout Linear pinning
Solder pins per potential 1
Data management status
Article revision 00
Electrical propertiesNominal current I_N 17.5 A
Nominal voltage U_N 400 V
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 400 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection dataConnection technology
Type PC terminal block can be aligned
Nominal cross section 2.5 mm²
Conductor connection
Connection method Spring-cage connection
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²
Stripping length 7 mm
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface terminal point (top layer) Tin (10 - 16 µm Sn)
Metal surface soldering area (top layer) Ti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKKDSA 2,5-5,08- 8 BKBDWH18-31 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.