

INDUSTRIAL COMPONENT DATA

590.EL2506 SCAME SWITCH DISCONNECTOR 25A 6P IP65

Brand: SCAME | Manufacturer Part Number: 590.EL2506



Manufacturer	SCAME
MPN / Reference	590.EL2506
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-BAC3D25EE8
Generated	2026-08-05

Product Overview

SWITCH DISCONNECTOR 25A 6P IP65
MANOEUVRING INT. 25A 6P IP66/IP69
25A 6P IP66/IP69 160x220x115mm Y3 IK09 GENERAL YELLOW/RED LOCKABLE ON-OFF GW 650°C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SCAME > Switches - SCAME
--------------	--------------------------

Additional Product Information

Commercial SeriesISOLATORS-TP SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialENGINEERING PLASTICProtection degreeIP66/IP69Installation temperature-25°C/+60°CTypeGENERALColourYELLOW/REDRated current25APoles6PSwitch sizeY3Rated voltage690VDimensions160x220x115mmNotes1LOCKABLE ON-OFFGLOW WIREGW 650°CProtection degreeIKIK09Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)8kVThermal current (Ithe)32ACurrent (Ie) in AC21A (415V)32ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)25ACurrent (Ie) in AC22A (500V)25ACurrent (Ie) in AC22A (690V)25ACurrent (Ie) in AC23A (415V)25ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25APower AC23A (415V)11kWShort-time current1,1kAlcw(1s)Conditional short circuit cur.50kAeffAssociate fuse - type gG25ATerminals - Flexible wires2.5-16mm²Terminals - Rigid wires2.5-16mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockBlank side with drilling point marks on top side baseBreak-through cable entries on bottom side baseReversible base

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.EL2506 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.