

INDUSTRIAL COMPONENT DATA

590.EL4015 SCAME SWITCH DISCONNECTOR 40A 3P+N IP65

Brand: SCAME | Manufacturer Part Number: 590.EL4015



Manufacturer	SCAME
MPN / Reference	590.EL4015
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-18457DE46B
Generated	2026-08-01

Product Overview

SWITCH DISCONNECTOR 40A 3P+N IP65
MANOEUVRING INT. 40A 3P+N IP66/IP69
40A 3P+N IP66/IP69 110x150x87mm Y1 IK09 GENERAL YELLOW/RED LOCKABLE ON-OFF GW 650°C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SCAME > Switches - SCAME
--------------	--------------------------

Additional Product Information

Commercial SeriesISOLATORS-TP SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialENGINEERING PLASTICProtection degreeIP66/IP69Installation temperature-25°C/+60°CTypeGENERALColourYELLOW/REDRated current40APoles3P+NSwitch sizeY1Rated voltage690VDimensions110x150x87mmNotes1LOCKABLE ON-OFFGLOW WIREGW 650°CProtection degreeIKIK09Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)40ACurrent (Ie) in AC22A (500V)32ACurrent (Ie) in AC22A (690V)32ACurrent (Ie) in AC23A (415V)35ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25ACurrent (Ie) in AC3 (415V)28.5ACurrent (Ie) in AC3 (690V)20ACurrent (Ie) in DC22A (250V)32ACurrent (Ie) in DC22A (600V)10APower AC23A (415V)18.5kWShort-time current400A Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG40ATerminals - Flexible wires1.5-10mm²Terminals - Rigid wires1.5-16mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockWith late break and early make neutral poleBlank side with drilling point marks on top side baseBreak-through cable entries on bottom side baseReversible base

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.EL4015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.