

INDUSTRIAL COMPONENT DATA**590.HEL1606 SCAME SWITCH DISCONNECTOR 16A 6P IP65**

Brand: SCAME | Manufacturer Part Number: 590.HEL1606



Manufacturer	SCAME
MPN / Reference	590.HEL1606
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-10FD1E97EB
Generated	2026-08-02

Product Overview

SWITCH DISCONNECTOR 16A 6P IP65

MANOEUVRING INT. 16A 6P IP66 GENERAL

16A 6P IP66 150x210x107mm Y3 IK10 GENERAL YELLOW/RED LOCKABLE ON-OFF

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SCAME > Switches - SCAME

Additional Product Information

Commercial SeriesISOLATORS-AL SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialDIE-CAST ALUMINIUMProtection degree IP65Installation temperature-25°C/+60°CTypeGENERALColourYELLOW/REDRated current16APoles6PSwitch sizeY3Rated voltage690VDimensions150x210x107mmNotes1LOCKABLE ON-OFFProtection degree IKIK10Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)8kVThermal current (Ithe)20ACurrent (Ie) in AC21A (415V)20ACurrent (Ie) in AC21A (500V)20ACurrent (Ie) in AC21A (690V)20ACurrent (Ie) in AC22A (415V)16ACurrent (Ie) in AC22A (500V)16ACurrent (Ie) in AC22A (690V)16ACurrent (Ie) in AC23A (415V)16ACurrent (Ie) in AC23A (500V)16ACurrent (Ie) in AC23A (690V)16APower AC23A (415V)7.5kWShort-time current1,1kA Icw(1s)Conditional short circuit cur.50kAeffAssociate fuse - type gG16ATerminals - Flexible wires2.5-16mm²Terminals - Rigid wires2.5-16mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockBlank sides

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.HEL1606 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.