

INDUSTRIAL COMPONENT DATA

590.HEL4006 SCAME SWITCH DISCONNECTOR 40A 6P IP65

Brand: SCAME | Manufacturer Part Number: 590.HEL4006



Manufacturer	SCAME
MPN / Reference	590.HEL4006
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7F2D39374D
Generated	2026-08-05

Product Overview

SWITCH DISCONNECTOR 40A 6P IP65

MANOEUVRING INT. 40A 6P IP66 GENERAL

40A 6P IP66 150x210x107mm Y3 IK10 GENERAL YELLOW/RED LOCKABLE ON-OFF

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathSCAME > Switches - SCAME

Additional Product Information

Commercial SeriesISOLATORS-AL SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialDIE-CAST ALUMINIUMProtection degree IP66Installation temperature-25°C/+60°CTypeGENERALColourYELLOW/REDRated current40APoles6PSwitch sizeY3Rated voltage690VDimensions150x210x107mmNotes1LOCKABLE ON-OFFProtection degree IKIK10Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)8kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)40ACurrent (Ie) in AC21A (690V)40ACurrent (Ie) in AC22A (415V)40ACurrent (Ie) in AC22A (500V)40ACurrent (Ie) in AC22A (690V)40ACurrent (Ie) in AC23A (415V)40ACurrent (Ie) in AC23A (500V)40ACurrent (Ie) in AC23A (690V)25APower AC23A (415V)18.5kWShort-time current1,1kA Icw(1s)Conditional short circuit cur.50kAeffAssociate fuse - type gG40ATerminals - Flexible wires2.5-16mm²Terminals - Rigid wires2.5-16mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockBlank sides

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.HEL4006 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.