

## INDUSTRIAL COMPONENT DATA

## 590.HEL6303 SCAME SWITCH DISCONNECTOR 63A 3P IP65

Brand: SCAME | Manufacturer Part Number: 590.HEL6303



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.HEL6303         |
| Catalog number  | 10000               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-70FB505C88       |
| Generated       | 2026-08-04          |

## Product Overview

SWITCH DISCONNECTOR 63A 3P IP65  
MANOEUVRING INT. 63A 3P IP66 GENERAL  
63A 3P IP66 150x210x107mm Y2 IK10 GENERAL YELLOW/RED LOCKABLE ON-OFF

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |                          |
|--------------|--------------------------|
| Catalog path | SCAME > Switches - SCAME |
|--------------|--------------------------|

## Additional Product Information

Commercial SeriesISOLATORS-AL SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialDIE-CAST ALUMINIUMProtection degree IP66Installation temperature-25°C/+60°CTypeGENERALColourYELLOW/REDRated current63APoles3PSwitch sizeY2Rated voltage690VDimensions150x210x107mmNotes1LOCKABLE ON-OFFProtection degree IKIK10Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)63ACurrent (Ie) in AC21A (415V)63ACurrent (Ie) in AC21A (500V)63ACurrent (Ie) in AC21A (690V)63ACurrent (Ie) in AC22A (415V)63ACurrent (Ie) in AC22A (500V)63ACurrent (Ie) in AC22A (690V)63ACurrent (Ie) in AC23A (415V)63ACurrent (Ie) in AC23A (500V)40ACurrent (Ie) in AC23A (690V)30ACurrent (Ie) in AC3 (415V)40ACurrent (Ie) in AC3 (690V)25ACurrent (Ie) in DC22A (250V)63APower AC23A (415V)33kWShort-time current1,5kA Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG63ATerminals - Flexible wiresTerminals - Rigid wires10-35mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockOpen threaded cable entry with cap / cable sleeve

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.HEL6303 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.