

## INDUSTRIAL COMPONENT DATA

# 590.KGEB12505 SCAME SWITCH DISCONNECTOR IP65 125A 3P+N

Brand: SCAME | Manufacturer Part Number: 590.KGEB12505



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.KGEB12505       |
| Catalog number  | 12505               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-049DBEC2EA       |
| Generated       | 2026-08-05          |

## Product Overview

SWITCH DISCONNECTOR IP65 125A 3P+N

MANOEUVRING INT. 125A 3P+N KF2 IP65

125A 3P+N IP65 BS 300x500x200mm KF2 IK10 GENERAL GREY/BLACK FUSE: BS

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SCAME &gt; Switches - SCAME

## Additional Product Information

Commercial SeriesISOLATORS-HR SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialMETALProtection degree IIP65Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current125APoles3P+NSwitch sizeKF2Fuse typeBSRated voltage690VDimensions300x500x200mmNotesFUSE: BSProtection degree IKIK10Rated insulation voltage (Ui)1000VAC1500VDCRated impulse voltage (Uimp)12KVThermal current (Ithe)125ACurrent (Ie) in AC21A (415V)125ACurrent (Ie) in AC21A (500V)125ACurrent (Ie) in AC21A (690V)125ACurrent (Ie) in AC22A (415V)125ACurrent (Ie) in AC22A (500V)125ACurrent (Ie) in AC22A (690V)125ACurrent (Ie) in AC23A (415V)125ACurrent (Ie) in AC23A (500V)100ACurrent (Ie) in AC23A (690V)80ACurrent (Ie) in DC21A (220V)125ACurrent (Ie) in DC21A (400V)125ACurrent (Ie) in DC22A (220V)125ACurrent (Ie) in DC23A (220V)125ACurrent (Ie) in DC23A (400V)125AConditional short circuit cur.50kAeffAssociate fuse - type gG125ATerminal bolt sizeM8Palm width21mmCatalogue notesTOP/BOTTOM = Top/Bottom connectionEquipped with door interlockHandle padlockable in OFF position only (3 padlocks)Fuses not suppliedWith late break and early make neutral poleGland plate cable entry on bottom side

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.KGEB12505 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.