

## INDUSTRIAL COMPONENT DATA

# 590.SEM16005 SCAME SWITCH DISCONNECTOR 160A 3P+N IP55

Brand: SCAME | Manufacturer Part Number: 590.SEM16005



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.SEM16005        |
| Catalog number  | 16005               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-14A4E9E7E9       |
| Generated       | 2026-08-03          |

## Product Overview

SWITCH DISCONNECTOR 160A 3P+N IP55  
MANOEUVRING INT. 160A 3P+N IP55  
160A 3P+N IP65 300x400x150mm Y5 IK10 EMERGENCY YELLOW/RED

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                          |
|--------------|--------------------------|
| Catalog path | SCAME > Switches - SCAME |
|--------------|--------------------------|

## Additional Product Information

Commercial SeriesISOLATORS-INOX SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialSTAINLESS STEEL [AISI304L]Protection degree IP65Installation temperature-25°C/+60°CTypeEMERGENCYColourYELLOW/REDRated current160APoles3P+NSwitch sizeY5Rated voltage690VDimensions300x400x150mmProtection degree IKIK10Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)8kVThermal current (Ithe)160ACurrent (Ie) in AC21A (415V)160ACurrent (Ie) in AC21A (500V)160ACurrent (Ie) in AC21A (690V)160ACurrent (Ie) in AC22A (415V)160ACurrent (Ie) in AC22A (500V)160ACurrent (Ie) in AC22A (690V)125ACurrent (Ie) in AC23A (415V)160ACurrent (Ie) in AC23A (500V)125ACurrent (Ie) in AC23A (690V)125APower AC23A (415V)69kWShort-time current3kA Icw(1s)Conditional short circuit cur.50kAeffAssociate fuse - type gG125ATerminals - Flexible wires10-70mm²Terminals - Rigid wires10-70mm²Catalogue notesBlank sidesEquipped with door interlockHandle padlockable in OFF position only (3 padlocks)With late break and early make neutral pole

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.SEM16005 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.