

## INDUSTRIAL COMPONENT DATA

# 590.SGE2503-C SCAME ISOLAT.25A 3P IP65 SURF.M.PLAST.BOX GEN

Brand: SCAME | Manufacturer Part Number: 590.SGE2503-C



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.SGE2503-C       |
| Catalog number  | 10000               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-9CF6F4416D       |
| Generated       | 2026-08-04          |

## Product Overview

ISOLAT.25A 3P IP65 SURF.M.PLAST.BOX GEN  
MANOEUVRING INT. 25A 3P  
25A 3P IP65 250x280x120mm C1 IK10 GENERAL GREY/BLACK

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                          |
|--------------|--------------------------|
| Catalog path | SCAME > Switches - SCAME |
|--------------|--------------------------|

## Additional Product Information

Commercial SeriesISOLATORS-INOX SeriesSynthetical descriptionENCLOSED CHANGE OVER SWITCHConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialSTAINLESS STEEL [AISI304L]Protection degree IP65Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current25APoles3PSwitch sizeC1Rated voltage690VDimensions250x280x120mmProtection degree IKIK10Rated insulation voltage (Ui)800VACRated impulse voltage (Uimp)8kVThermal current (Ithe)32ACurrent (Ie) in AC21A (415V)32ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)25ACurrent (Ie) in AC22A (500V)25ACurrent (Ie) in AC22A (690V)25ACurrent (Ie) in AC23A (415V)25ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25APower AC23A (415V)11kWShort-time current1,1kA Icw(1s)Conditional short circuit cur.50kAeffAssociate fuse - type gG25ATerminals - Flexible wires2.5-16mm²Terminals - Rigid wires2.5-16mm²Catalogue notesBlank sidesEquipped with door interlockHandle padlockable in OFF position only (3 padlocks)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.SGE2503-C with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.