

INDUSTRIAL COMPONENT DATA**590.GE4008 SCAME SWITCH DISCONNECTOR 40A 8P IP65**

Brand: SCAME | Manufacturer Part Number: 590.GE4008



Manufacturer	SCAME
MPN / Reference	590.GE4008
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7BEAA012DF
Generated	2026-07-31

Product Overview

SWITCH DISCONNECTOR 40A 8P IP65

MANOEUVRING INT. 40A 8P IP66/IP69

40A 8P IP66/IP69 160x220x115mm Y3 IK09 GENERAL GREY/BLACK GW 650°C

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathSCAME > Switches - SCAME

Additional Product Information

Commercial SeriesISOLATORS-TP SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialENGINEERING PLASTICProtection degreeIP66/IP69Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current40APoles8PSwitch sizeY3Rated voltage690VDimensions160x220x115mmGLOW WIREGW 650°CProtection degree IKIK09Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)8kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)40ACurrent (Ie) in AC21A (690V)40ACurrent (Ie) in AC22A (415V)40ACurrent (Ie) in AC22A (500V)40ACurrent (Ie) in AC22A (690V)40ACurrent (Ie) in AC23A (415V)40ACurrent (Ie) in AC23A (500V)40ACurrent (Ie) in AC23A (690V)25APower AC23A (415V)18.5kWShort-time current1,1kA Icw(1s)Conditional short circuit cur.50kAeffAssociate fuse - type gG40ATerminals - Flexible wires2.5-16mm²Terminals - Rigid wires2.5-16mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockWith late break and early make neutral poleBlank side with drilling point marks on top side baseBreak-through cable entries on bottom side baseReversible base

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.GE4008 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.