

INDUSTRIAL COMPONENT DATA

590.GE4012 SCAME ISOLAT.40A 2P IP65 SURF.M.PLAST.BOX GEN

Brand: SCAME | Manufacturer Part Number: 590.GE4012



Manufacturer	SCAME
MPN / Reference	590.GE4012
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-FA580F4295
Generated	2026-08-02

Product Overview

ISOLAT.40A 2P IP65 SURF.M.PLAST.BOX GEN
MANOEUVRING INT 40A 2P IP66/IP69
40A 2P IP66/IP69 110x150x87mm Y1 IK09 GENERAL GREY/BLACK GW 650°C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SCAME > Switches - SCAME

Additional Product Information

Commercial SeriesISOLATORS-TP SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialENGINEERING PLASTICProtection degree IP66/IP69Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current40APoles2PSwitch sizeY1Rated voltage690VDimensions110x150x87mmGLOW WIREGW 650°CProtection degree IKIK09Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)40ACurrent (Ie) in AC22A (500V)32ACurrent (Ie) in AC22A (690V)32ACurrent (Ie) in AC23A (415V)35ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25ACurrent (Ie) in AC3 (415V)28.5ACurrent (Ie) in AC3 (690V)20ACurrent (Ie) in DC22A (250V)32ACurrent (Ie) in DC22A (600V)10APower AC23A (415V)18.5kWShort-time current400A Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG40ATerminals - Flexible wires1.5-10mm²Terminals - Rigid wires1.5-16mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockBlank side with drilling point marks on top side baseBreak-through cable entries on bottom side baseReversible base

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.GE4012 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.