

## INDUSTRIAL COMPONENT DATA

## 590.GR3205 SCAME SWITCH DISCONNECTOR 32A 3P+N IP65

Brand: SCAME | Manufacturer Part Number: 590.GR3205



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.GR3205          |
| Catalog number  | 10000               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-28347E9F14       |
| Generated       | 2026-07-29          |

## Product Overview

SWITCH DISCONNECTOR 32A 3P+N IP65  
MANOEUVRING INT. 32A 3P+N IP65 136x125mm  
32A 3P+N IP65 136x125mm Y1 IK09 GENERAL GREY/BLACK GW 650°C

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |                          |
|--------------|--------------------------|
| Catalog path | SCAME > Switches - SCAME |
|--------------|--------------------------|

## Additional Product Information

Commercial SeriesISOLATORS-TP SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionFLUSH MOUNTINGMaterialENGINEERING PLASTICProtection degree IPIP65Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current32APoles3P+NSwitch sizeY1Rated voltage690VDimensions136x125mmGLOW WIREGW 650°CProtection degree IKIK09Flange136X125MMRated insulation voltage (Ui)690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)32ACurrent (Ie) in AC22A (500V)32ACurrent (Ie) in AC22A (690V)32ACurrent (Ie) in AC23A (415V)32ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25ACurrent (Ie) in AC3 (415V)25ACurrent (Ie) in AC3 (690V)18ACurrent (Ie) in DC22A (250V)32ACurrent (Ie) in DC22A (600V)10APower AC23A (415V)15kWShort-time current400A Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG32ATerminals - Flexible wires1.5-10mm<sup>2</sup>Terminals - Rigid wires1.5-16mm<sup>2</sup>Catalogue notesWith late break and early make neutral poleHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionWith panel mounting version (R) switch

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.GR3205 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.