

## INDUSTRIAL COMPONENT DATA

# 590.HEM3204 SCAME ISOL. 32A 4P IP65 SURF.M.ALUM.BOX EMERG

Brand: SCAME | Manufacturer Part Number: 590.HEM3204



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.HEM3204         |
| Catalog number  | 10000               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-D0F945EF7C       |
| Generated       | 2026-07-31          |

## Product Overview

ISOL. 32A 4P IP65 SURF.M.ALUM.BOX EMERG  
SWITCHING INT. 32A 4P IP66 EMERGENCY  
32A 4P IP66 105x150x82mm Y1 IK10 EMERGENCY YELLOW/RED

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SCAME &gt; Switches - SCAME

## Additional Product Information

Commercial SeriesISOLATORS-AL SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialDIE-CAST ALUMINIUMProtection degree IP66Installation temperature-25°C/+60°CTypeEMERGENCYColourYELLOW/REDRated current32APoles4PSwitch sizeY1Rated voltage690VDimensions105x150x82mmProtection degree IK10Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)32ACurrent (Ie) in AC22A (500V)32ACurrent (Ie) in AC22A (690V)32ACurrent (Ie) in AC23A (415V)32ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25ACurrent (Ie) in AC3 (415V)25ACurrent (Ie) in AC3 (690V)18ACurrent (Ie) in DC22A (250V)32ACurrent (Ie) in DC22A (600V)10APower AC23A (415V)15kWShort-time current400A Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG32ATerminals - Flexible wires1.5-10mm<sup>2</sup>Terminals - Rigid wires1.5-16mm<sup>2</sup>Catalogue notesHandle padlockable in OFF position only (3 padlocks)Equipped with door interlockOpen threaded cable entry with cap / cable sleeve

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.HEM3204 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.