

## INDUSTRIAL COMPONENT DATA

# 590.HGE16008 SCAME SWITCH DISCONNECTOR 160A 8P IP65 MET

Brand: SCAME | Manufacturer Part Number: 590.HGE16008



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.HGE16008        |
| Catalog number  | 16008               |
| Category        | Switch disconnector |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-926B67B231       |
| Generated       | 2026-08-01          |

## Product Overview

SWITCH DISCONNECTOR 160A 8P IP65 MET  
MANOEUVRING INT. 160A 8P IP65 GENERAL  
160A 8P IP65 315x410x150mm Y5 IK08 GENERAL GREY/BLACK

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SCAME > Switches - SCAME

## Additional Product Information

Commercial SeriesISOLATORS-AL SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialDIE-CAST ALUMINIUMProtection degree IP65Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current160APoles8PSwitch sizeY5Rated voltage690VDimensions315x410x150mmProtection degree IKIK08Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)8kVThermal current (Ithe)160ACurrent (Ie) in AC21A (415V)160ACurrent (Ie) in AC21A (500V)160ACurrent (Ie) in AC21A (690V)160ACurrent (Ie) in AC22A (415V)160ACurrent (Ie) in AC22A (500V)160ACurrent (Ie) in AC22A (690V)125ACurrent (Ie) in AC23A (415V)160ACurrent (Ie) in AC23A (500V)125ACurrent (Ie) in AC23A (690V)125APower AC23A (415V)69kWShort-time current3kA Icw(1s)Conditional short circuit cur.50kAeffAssociate fuse - type gG125ATerminals - Flexible wires10-70mm²Terminals - Rigid wires10-70mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockBlank sidesWith late break and early make neutral pole

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.HGE16008 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.