

INDUSTRIAL COMPONENT DATA

590.HGE4005 SCAME SWITCH DISCONNECTOR 40A 3P+N IP65

Brand: SCAME | Manufacturer Part Number: 590.HGE4005



Manufacturer	SCAME
MPN / Reference	590.HGE4005
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-4E5F5B686B
Generated	2026-08-03

Product Overview

SWITCH DISCONNECTOR 40A 3P+N IP65
MANOEUVRING INT. 40A 3P+N IP66 GENERAL
40A 3P+N IP66 105x150x82mm Y1 IK10 GENERAL GREY/BLACK

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SCAME > Switches - SCAME

Additional Product Information

Commercial SeriesISOLATORS-AL SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialDIE-CAST ALUMINIUMProtection degree IP65Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current40APoles3P+NSwitch sizeY1Rated voltage690VDimensions105x150x82mmProtection degree IK10Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)40ACurrent (Ie) in AC22A (500V)32ACurrent (Ie) in AC22A (690V)32ACurrent (Ie) in AC23A (415V)35ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25ACurrent (Ie) in AC3 (415V)28.5ACurrent (Ie) in AC3 (690V)20ACurrent (Ie) in DC22A (250V)32ACurrent (Ie) in DC22A (600V)10APower AC23A (415V)18.5kWShort-time current400A Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG40ATerminals - Flexible wires1.5-10mm²Terminals - Rigid wires1.5-16mm²Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockWith late break and early make neutral poleOpen threaded cable entry with cap / cable sleeve

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.HGE4005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.