

## INDUSTRIAL COMPONENT DATA

# 590.HGE4008 SCAME SWITCH DISCONNECTOR 40A 8P IP65 MET

Brand: SCAME | Manufacturer Part Number: 590.HGE4008



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.HGE4008         |
| Catalog number  | 10000               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-D57E890AAD       |
| Generated       | 2026-08-03          |

## Product Overview

SWITCH DISCONNECTOR 40A 8P IP65 MET  
MANOEUVRING INT. 40A 8P IP66 GENERAL  
40A 8P IP66 150x210x107mm Y3 IK10 GENERAL GREY/BLACK

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                          |
|--------------|--------------------------|
| Catalog path | SCAME > Switches - SCAME |
|--------------|--------------------------|

## Additional Product Information

Commercial SeriesISOLATORS-AL SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialDIE-CAST ALUMINIUMProtection degree IP65Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current40APoles8PSwitch sizeY3Rated voltage690VDimensions150x210x107mmProtection degree IKIK10Rated insulation voltage (Ui)690VACRated impulse voltage (Uimp)8kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)40ACurrent (Ie) in AC21A (690V)40ACurrent (Ie) in AC22A (415V)40ACurrent (Ie) in AC22A (500V)40ACurrent (Ie) in AC22A (690V)40ACurrent (Ie) in AC23A (415V)40ACurrent (Ie) in AC23A (500V)40ACurrent (Ie) in AC23A (690V)25APower AC23A (415V)18.5kWShort-time current1,1kA l<sub>cw</sub>(1s)Conditional short circuit cur.50kA<sub>eff</sub>Associate fuse - type gG40ATerminals - Flexible wires2.5-16mm<sup>2</sup>Terminals - Rigid wires2.5-16mm<sup>2</sup>Catalogue notesHandle padlockable in OFF (3 padlocks) and ON (1 padlock) positionEquipped with door interlockBlank sidesWith late break and early make neutral pole

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.HGE4008 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.