

INDUSTRIAL COMPONENT DATA

590.JEM4002 SCAME SWITCH DISCONNECTOR 40A 2P IP66

Brand: SCAME | Manufacturer Part Number: 590.JEM4002



Manufacturer	SCAME
MPN / Reference	590.JEM4002
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5DF1D1036E
Generated	2026-07-31

Product Overview

SWITCH DISCONNECTOR 40A 2P IP66

MANOEUVRING INT. 40A 2P IP66

40A 2P IP66 115x190x128mm Y1 IK10 EMERGENCY YELLOW/RED GW 960°C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SCAME > Switches - SCAME

Additional Product Information

Commercial SeriesISOLATORS-HD SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialENGINEERING PLASTICProtection degree IP66Installation temperature-25°C/+60°CTypeEMERGENCYColourYELLOW/REDRated current40APoles2PSwitch sizeY1Rated voltage690VDimensions115x190x128mmGLOW WIREGW 960°CProtection degree IKIK10Ambient temperature Ta min-40 °CAmbient temperature Ta max60 °CRated insulation voltage (Ui)690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)40ACurrent (Ie) in AC22A (500V)32ACurrent (Ie) in AC22A (690V)32ACurrent (Ie) in AC23A (415V)35ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25ACurrent (Ie) in AC3 (415V)28.5ACurrent (Ie) in AC3 (690V)20ACurrent (Ie) in DC22A (250V)32ACurrent (Ie) in DC22A (600V)10APower AC23A (415V)18.5kWSShort-time current400A Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG40ATerminals - Flexible wires1.5-10mm²Terminals - Rigid wires1.5-16mm²Catalogue notesBlank side with drilling point marksHandle padlockable in OFF (3 padlocks) and ON (1 padlock) position

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.JEM4002 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.