

## INDUSTRIAL COMPONENT DATA

## 590.JGE3202 SCAME SWITCH DISCONNECTOR 32A 2P IP66

Brand: SCAME | Manufacturer Part Number: 590.JGE3202



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SCAME               |
| MPN / Reference | 590.JGE3202         |
| Catalog number  | 10000               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-6E03739D3E       |
| Generated       | 2026-07-31          |

## Product Overview

SWITCH DISCONNECTOR 32A 2P IP66

32A 2P IP66 115x190x128mm Y1 IK10 GENERAL GREY/BLACK GW 960°C

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog pathSCAME &gt; Switches - SCAME

## Additional Product Information

Commercial SeriesISOLATORS-HD SeriesSynthetical descriptionSWITCH DISCONNECTORConstruction typeEnclosedMounting versionSURFACE MOUNTINGMaterialENGINEERING PLASTICProtection degree IP66Installation temperature-25°C/+60°CTypeGENERALColourGREY/BLACKRated current32APoles2PSwitch sizeY1Rated voltage690VDimensions115x190x128mmGLOW WIREGW 960°CProtection degree IK10Ambient temperature Ta min-40 °CAmbient temperature Ta max60 °CRated insulation voltage (Ui)690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)40ACurrent (Ie) in AC21A (415V)40ACurrent (Ie) in AC21A (500V)32ACurrent (Ie) in AC21A (690V)32ACurrent (Ie) in AC22A (415V)32ACurrent (Ie) in AC22A (500V)32ACurrent (Ie) in AC22A (690V)32ACurrent (Ie) in AC23A (415V)32ACurrent (Ie) in AC23A (500V)25ACurrent (Ie) in AC23A (690V)25ACurrent (Ie) in AC3 (415V)25ACurrent (Ie) in AC3 (690V)18ACurrent (Ie) in DC22A (250V)32ACurrent (Ie) in DC22A (600V)10APower AC23A (415V)15kWShort-time current400A Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG32ATerminals - Flexible wires1.5-10mm<sup>2</sup>Terminals - Rigid wires1.5-16mm<sup>2</sup>Catalogue notesBlank side with drilling point marksHandle padlockable in OFF (3 padlocks) and ON (1 padlock) position

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.JGE3202 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.