

INDUSTRIAL COMPONENT DATA

590.YF162B SCAME SWITCHING UNIT BASE MOUNT.W/FUSE 16A 2P

Brand: SCAME | Manufacturer Part Number: 590.YF162B



Manufacturer	SCAME
MPN / Reference	590.YF162B
Catalog number	10000
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-320504B3F4
Generated	2026-07-29

Product Overview

SWITCHING UNIT BASE MOUNT.W/FUSE 16A 2P
BODY INT. MAN. WITH PORTAFUS. 16A 2P B
16A 2P gG 10,3x38mm F1 BOX (B)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SCAME > Switches - SCAME
--------------	--------------------------

Additional Product Information

Commercial SeriesCOMMAND SeriesSynthetical descriptionSWITCH DISCONNECTOR FUSEConstruction typeOpen typeMounting versionBMaterialTHERMOPLASTICInstallation temperature-25°C/+60°CTypeBOX (B)Rated current16APoles2PSwitch sizeF1Fuse typегG 10,3x38mmRated voltage690VRated insulation voltage (Ui)400VDC690VACRated impulse voltage (Uimp)4kVThermal current (Ithe)16ACurrent (Ie) in AC21A (415V)16ACurrent (Ie) in AC21A (500V)16ACurrent (Ie) in AC21A (690V)16ACurrent (Ie) in AC22A (415V)16ACurrent (Ie) in AC22A (500V)16ACurrent (Ie) in AC22A (690V)16ACurrent (Ie) in AC23A (415V)16ACurrent (Ie) in AC23A (500V)16ACurrent (Ie) in AC23A (690V)16ACurrent (Ie) in AC3 (415V)18APower AC23A (415V)7.5kWShort-time current400A Icw(1s)Conditional short circuit cur.10kAeffAssociate fuse - type gG16ATerminals - Flexible wires1.5-10mm²Terminals - Rigid wires1.5-16mm²Catalogue notesFuses not suppliedBOX (B) = Base mountingDIN rail fixing

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 590.YF162B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.