

**INDUSTRIAL COMPONENT DATA****839.39/9180 SCAME CABLE TIES FOR OUTDOOR USE 9X180**

Brand: SCAME | Manufacturer Part Number: 839.39/9180



|                 |               |
|-----------------|---------------|
| Manufacturer    | SCAME         |
| MPN / Reference | 839.39/9180   |
| Catalog number  | 83939         |
| Category        | Cable tie     |
| Minimum order   | 4 Pcs         |
| Document ID     | EO-D91A8E422C |
| Generated       | 2026-08-03    |

**Product Overview**

CABLE TIES FOR OUTDOOR USE 9X180  
SELF-LOCKING BRIDLE 9x180mm  
9x180mm BLACK

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                        |
|--------------|--------------------------------------------------------|
| Catalog path | SCAME > Installation accessories - SCAME > TIES Series |
|--------------|--------------------------------------------------------|

**Additional Product Information**

Commercial SeriesTIES SeriesSynthetical descriptionCABLE TIEMaterialENGINEERING  
PLASTICColourBLACKDimensions9x180mmClamping diameter10÷38mmTraction resistance40kgCatalogue notesRounded  
edges to avoid cutting into cable insulation.Good resistance to external agents: oil, grease, oil derivatives and saline  
mist.Withstands UV rays.SCAME cable ties load-elongation curve  
4 zones with different characteristics are clearly distinguished:  
1) Elastic elongation (area of use).  
The cable tie is subjected to traction forces and lengthens, elastically. When the forces are taken away, the tie returns to its  
initial state, without any alteration of its physical characteristics.  
2) Stretching of the molecular links.  
The tie is subjected to such a load that some of the intermolecular links are broken. The elastic properties are altered.  
3) Permanent deformity.  
All the inter-molecular links are broken.  
4) Breaking-point.  
Length at which the tie breaks.

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SCAME / 839.39/9180 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.