

INDUSTRIAL COMPONENT DATA

3KA7157-3AA00 SIEMENS SECTION 3x 3150 A SANS COMM

Brand: SIEMENS | Manufacturer Part Number: 3KA7157-3AA00



Manufacturer	SIEMENS
MPN / Reference	3KA7157-3AA00
Catalog number	71573
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-6BD68CF774
Generated	2026-08-01

Product Overview

SECTION 3x 3150 A SANS COMM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

ETIM: EC000216 - Switch disconnecter

Value Unit

Degree of protection (NEMA) (EF011959) -

Switching power at 400 V (EF009166) - kW

Rated operating voltage (EF001435) - V

Voltage release optional (EF007491) -

Suitable for intermediate mounting (EF007264) -

Colour control element (EF007167) -

Rated operation power at AC-23, 400 V (EF007027) - kW

Number of auxiliary contacts as normally open contact (EF001376) -

Rated permanent current at AC-23, 400 V (EF011777) - A

Suitable for front mounting 4-hole (EF007247) -

Version as reversing switch (EF009408) -

Number of auxiliary contacts as normally closed contact (EF001377) -

Version as main switch (EF006981) -

Number of auxiliary contacts as change-over contact (EF003531) -

Number of switches (EF005586) -
Type of control element (EF006976) -
Suitable for front mounting centre (EF007248) -
Version as maintenance-/service switch (EF006986) -
Rated operation power at AC-3, 400 V (EF001364) - kW
Suitable for distribution board installation (EF007262) -
Rated permanent current at AC-21, 400 V (EF009165) - A
Interlockable (EF006281) -
Rated short-time withstand current I_{cw} (EF007050) - kA
Motor drive optional (EF007386) -
Version as safety switch (EF006985) true
Version as emergency stop installation (EF006959) true
Max. rated operation voltage U_e AC (EF007355) 690 V
Rated permanent current I_u (EF001389) 3150.0 A
Conditioned rated short-circuit current I_q (EF001444) 100.0 kA
Number of poles (EF001391) 3
Motor drive integrated (EF006697) f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KA7157-3AA00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.