

## INDUSTRIAL COMPONENT DATA

**3KA7157-3AA00 SIEMENS SECTION 3x 3150 A SANS COMM**

Brand: SIEMENS | Manufacturer Part Number: 3KA7157-3AA00



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SIEMENS             |
| MPN / Reference | 3KA7157-3AA00       |
| Catalog number  | 71573               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-6BD68CF774       |
| Generated       | 2026-08-03          |

**Product Overview**

SECTION 3x 3150 A SANS COMM

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; SWITCHES-DISCONNECTORS

**Additional Product Information**

ETIM: EC000216 - Switch disconnecter

Value Unit

Degree of protection (NEMA) (EF011959) -

Switching power at 400 V (EF009166) - kW

Rated operating voltage (EF001435) - V

Voltage release optional (EF007491) -

Suitable for intermediate mounting (EF007264) -

Colour control element (EF007167) -

Rated operation power at AC-23, 400 V (EF007027) - kW

Number of auxiliary contacts as normally open contact (EF001376) -

Rated permanent current at AC-23, 400 V (EF011777) - A

Suitable for front mounting 4-hole (EF007247) -

Version as reversing switch (EF009408) -

Number of auxiliary contacts as normally closed contact (EF001377) -

Version as main switch (EF006981) -

Number of auxiliary contacts as change-over contact (EF003531) -

Number of switches (EF005586) -  
Type of control element (EF006976) -  
Suitable for front mounting centre (EF007248) -  
Version as maintenance-/service switch (EF006986) -  
Rated operation power at AC-3, 400 V (EF001364) - kW  
Suitable for distribution board installation (EF007262) -  
Rated permanent current at AC-21, 400 V (EF009165) - A  
Interlockable (EF006281) -  
Rated short-time withstand current I<sub>cn</sub> (EF007050) - kA  
Motor drive optional (EF007386) -  
Version as safety switch (EF006985) true  
Version as emergency stop installation (EF006959) true  
Max. rated operation voltage U<sub>e</sub> AC (EF007355) 690 V  
Rated permanent current I<sub>n</sub> (EF001389) 3150.0 A  
Conditioned rated short-circuit current I<sub>k</sub> (EF001444) 100.0 kA  
Number of poles (EF001391) 3  
Motor drive integrated (EF006697) f...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KA7157-3AA00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.