

INDUSTRIAL COMPONENT DATA

3KC3432-2AA22-0AA3 SIEMENS SENTRON, transfer switching equipment 3KC, remotely operated, RTSE, 4-pole, lu: 1..

Brand: SIEMENS | Manufacturer Part Number: 3KC3432-2AA22-0AA3



Manufacturer	SIEMENS
MPN / Reference	3KC3432-2AA22-0AA3
Catalog number	34322
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-69FD3942D6
Generated	2026-08-05

Product Overview

SENTRON, transfer switching equipment 3KC, remotely operated, RTSE, 4-pole, lu: 125 A, Ue AC: 415 V, Ie at AC-33 B at 415 V: 125 A, Ie at AC-23 A at 690 V: 80 A, screw and standard mounting rail on 35 mm, motorized operating mechanism, at the right end, long handle, box terminal

RTSE RTSE TRANSFER SWITCH, 125A, 4 POLES FRONT ACCONAMIENTO BASE UNIT WITH HANDLE 2X POWER 230V AC FRAME TERMINALS. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3KD Switch-disconnectors, 3KC Pow

Additional Product Information

ETIM: EC000216 - Switch disconnecter

Value Unit

Rated permanent current at AC-23, 400 V (EF011777) - A

Version as main switch (EF006981) true

Version as maintenance-/service switch (EF006986) true

Version as safety switch (EF006985) false

Version as emergency stop installation (EF006959) false

Version as reversing switch (EF009408) -

Number of switches (EF005586) -

Max. rated operation voltage Ue AC (EF007355) 415 V

Rated operating voltage (EF001435) ['176.0', '288.0'] V

Rated permanent current I_u (EF001389) 125.0 A
Rated permanent current at AC-21, 400 V (EF009165) 125 A
Rated short-time withstand current I_{cw} (EF007050) 4.0 kA
Number of poles (EF001391) 4
Number of auxiliary contacts as normally closed contact (EF001377) 0
Number of auxiliary contacts as normally open contact (EF001376) 0
Number of auxiliary contacts as change-over contact (EF003531) 3
Motor drive optional (EF007386) false
Motor drive integrated (EF006697) true
Voltage release optional (EF007491) false
Device construction (EF008240) Built-in device fixed built-in technique
Suitable for floor mounting (EF007243) FALSE
Suitable for front mounting 4-hole (EF007247) false
Suitable for front mounting centre (EF007248) false
Suitable for distribution board installation (EF007262) true
Suitable for intermediate mounting (EF007264) true
Colour control element (EF007167) Black
Type of control element (EF006976) Long turning handle
Interlockable (EF006281) true
Type of electrical connection of main circuit (EF006819)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KC3432-2AA22-0AA3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.